

PRODUCT DATA SHEET



826 BI-DIRECTIONAL FILAMENT TAPE Single Sided Polypropylene

Product Features:

- * High cross direction tensile strength backing.
- * Aggressive shear resistant adhesive.
- * Strong fibreglass reinforced filaments.
- * Excellent adhesion for cold weather and humidity resistance.
- * Good chemical and moisture resistance.

Applications:

- * Heavy duty palletising.
- * Packaging and wrapping.
- * Strapping and bundling.

Product Specifications:

*	Adhesive:	Rubber resin
*	Backing:	Polypropylene with cross link fibreglass filaments
*	Backing thickness:	0.10mm
*	Total thickness:	0.13mm
*	Colours:	Cream
*	Tensile strength:	575N per 25mm
*	Adhesion to steel:	25N per 25mm
*	Temperature resistance:	60 deg C.
*	Elongation:	6%

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.